

Junckers Sports Floor Cleaning & Maintenance Guide



ENTRANCE BARRIER MATTING

Junckers recommends that good quality entrance barrier mats are used at all external entrances to the flooring to collect grit and moisture from the underside of footwear. We strongly recommend that at least 2—3 foot falls are allowed for. Vacuum and clean the mat regularly.

FOOTWEAR

Junckers floors are hard wearing, but we recommend that when the floor is being used for sports use that black soled shoes are avoided as these can leave unsightly marks on the surface of the floor. Any black marks can be removed easily by normal cleaning if tackled the same day. If left, then use a cloth with a little white spirit to dissolve them. Please consult Junckers for advice on other uses such as roller skating, trampolining and other social activities such as parties, bouncy castles etc.

MATS AND PROTECTIVE PADS

USE Junckers felt pads or carpet based castor cups under chair and table legs. Place protective matting under chair wheels at areas of extreme concentration and wear. Alternatively, consider the use of canvas druggert mats if the floor is being used for another function.

SPILLAGES

Junckers hardwood floors have a level of water resistance; however damage can occur if spillages of liquid onto the surface are not wiped up immediately. Extra coats of site applied lacquer will increase the water resistance of the floor, however it will not be waterproof.

DAILY

Sweep once or twice a day with V sweepers or vacuum the floor to collect and remove dirt and abrasive materials. Ensure that if a sweeper is used it is regularly vacuumed to maintain effective dirt and dust removal. Remove gum and black rubber shoe marks daily.

DAILY, WEEKLY OR PERIODICALLY

Comprehensively auto scrub/dry the floor using Junckers Cleaner diluted with water in accordance with the instructions printed on the packaging. Make sure excess water is not used and is automatically vacuumed up during the cleaning process.

If a rotary cleaning machine is used, ensure that only white pads are fitted and that any surplus water is vacuumed up immediately.

We do not recommend the use of mop and buckets to clean the whole floor on a regular basis, however at various times during the day some flat damp mopping will naturally take place to deal with localised spillages.

STAIR TREADS

Wooden stair treads will require separate consideration. In addition to the cleaning routine described above we recommend that stair treads are abrasive screen meshed, cleaned and a coat of Junckers High Performance polyurethane seal be applied every 12 months.



Junckers approved maintenance contractors & product suppliers:

Olympic Gymnasium Services
Tel: 01295 760192 Fax: 01295 768092
e-mail: sales@olympicgymnasium.com
www.olympicgymnasium.com

JUNCKERS

Junckers Sports Floor Cleaning & Maintenance Guide



CONDITIONS

We recommend that the humidity of the air be maintained in the range 35-65% relative humidity and that the air temperature be maintained at 16 to 22 degrees centigrade.

Please note that especially for new buildings it may be necessary to run the heating and ventilation systems at a higher rate to dry out any residual moisture in the building.

In the summer months it is recommended that to reduce a build of high humidity that ventilation be carried out in the evening or at night.

In the winter ventilate only to maintain the freshness of the air.

Do not shut the room up without sufficient ventilation or for long periods of time as this will affect the moisture content of the flooring. This is particularly important in new buildings or buildings which remain unoccupied for long periods of time.

Do not cover floors up with polythene or similar materials for long periods of time and do not use adhesive tapes on the floor as their removal may affect the adhesion of the seal. We recommend painted line markings for sports use. If temporary taped markings are needed then only use very low contact adhesive tapes compatible with lacquered flooring.

Loading: Junckers floors are designed to withstand loadings of 5KN/m². Please consult with Junckers for advice on any loadings other than normal foot traffic.

PERIODICALLY

We recommend that the floors surface be inspected by the Approved Contractor every 6 months for the build up of any soap, dirt or grease deposits which will make the floor slippery. If this is the case we recommend that the floor be thoroughly cleaned using Junckers Degreasing products, and afterwards using Junckers Cleaner all in accordance with the instructions printed on the packaging. Only regular cleaning prevents slippery conditions to all floors.

LONG-TERM: RESEALING

We recommend that the floors surface be inspected by the Approved Contractor every 12 to 18 months to inspect the condition of the seal and the surface of the wood. We recommend after this inspection that the floor be screen mesh abraded, and 1 coat of Junckers polyurethane seal be applied. This will prolong the life of any line markings and guarantee them for 5 years.

LONG-TERM: SAND AND SEAL

Providing that the above maintenance procedure is followed the floor may not need sanding for many years. However, damage to the surface of the floor can occur so we recommend that the floors surface be continually reviewed and if necessary the surface can be sanded and sealed.

For budget purposes we would recommend for normal average use that the floors surface may need to be sanded and sealed approximately every 7 to 10 years. Minor repairs can be taken care of at this time. If it is deemed necessary to do this then we recommend that the floor be sanded back to bare wood before applying a Junckers 3-4 coat polyurethane sealing system. Junckers line marking paint can be applied between the top 2 coats of seal.



Junckers approved maintenance contractors & product suppliers:

Olympic Gymnasium Services
Tel: 01295 760192 Fax: 01295 768092
e-mail: sales@olympicgymnasium.com
www.olympicgymnasium.com


JUNCKERS